

UKIT SHW042-75W

PRODUCT DESCRIPTION

The UKit offers a simple and universal build that allows the LED plates to be easily mounted in virtually any fixture. From downlights to parking lot lights, they can be installed in most applications.

FEATURES


All aluminum construction Easy tab mounting Simple build design Color temperature options

PERFORMANCE SUMMARY

Lumens: 8475 Lumens per Watt: 113 CRI-Minimum: >70 CCT: 3000K ,4000K ,5000K Dimming: 0-10V (standard) Operating Environment: -40C to 60C Optical Distribution: 120 distribution Wattage: 75

PERFORMANCE RATINGS AND CERTIFICATIONS

ETL ,DLC



KIT INFORMATION

Finish: Aluminum Finish
Mounting: Universal mounting kit with four 2.5", four 4.75" and four 7.5" magic tabs.
Dimensions: 9.0" x 9.0" x 2.65"
Weight: 1.26 lbs.
Fits in with Internal Dimensions: 9" – 24" x 9" – 24" x 3" (minimum)

ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120 - 277VAC Dimming: 0-10V (standard) Power Factor: > 0.98 Total Harmonic Distortion: < 20%

WARRANTY

5 Year Standard Warranty Limited

Specifications are subject to change at any time without notice. For more information and product support, contact GenPro Advanced Technologies at 800.465.1286 or email info@GenProTech.com

Copyright GenPro Technologies

www.GenProTech.com



ORDERING MATRIX

Family	Product	Board Shape	Watts	Color Temp	Voltage	Options	Mounting	Optical Distribution
Universal Kit	UKit	SHW042-75W	75W	30 = 3000K 40 = 4000K 50 = 5000K	MT = 120-277VV	010V = 0-10V Dimming (standard)		

PHOTOMETRICS