

PRODUCT DESCRIPTION

The LED Floodlight (FLV1) are ideal for illuminating building exteriors, architectural monuments and outdoor objects like billboards, highway signs etc. These fixtures feature a die cast aluminum housing with hinged top frame and tempered clear glass lens. This light is IP65 rated and is suitable for Wet locations.

FEATURES

Long life, low maintenance, and high efficiency

IP65 Rated

5 Year Warranty

PERFORMANCE RATINGS AND CERTIFICATIONS

UL, cUL, DLC

PERFORMANCE SUMMARY

Lumens: 4000, 5763

Lumens per Watt: >115 lm/W

CRI-Minimum: >70

CCT: Cool White (5700K), Natural White (4000K)

Watts: 30W, 50W

Operating Environment: -20°C to 45°C

Optical Distribution: 110° Beam Angle



KIT INFORMATION

Finish: Bronze

Mounting: Knuckle Mount included, Yoke Mount (optional)

Dimensions: 7.91" x 8.54" x 1.89"

ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120 - 277VAC, 50/60 Hz

Dimming:

Power Factor: >0.9

Total Harmonic Distortion: ≤20%

WARRANTY

5 Year Standard Warranty Limited

ORDERING MATRIX

Example: ST-FLV1-50W-NW-MT-YM

Family	Product	Watts	Color Temp	Voltage	Mounting
ST	FLV1 = LED Floodlight	30W 50W	CW = Cool White (5700K) NW = Natural White (4000K)	MT = 120-277VAC 50/60 Hz	Standard Knuckle Mount is included YM = Yoke Mount Bracket